



शुक्लागण्डकी नगरपालिका
नगर कार्यपालिकाको कार्यालय
दुलेगौडा, तनहुँ
गण्डकी प्रदेश, नेपाल

सुचना नं. : ७०

मिति: २०८३/०२/०८


विषय: दरभाउ पत्र पेश गर्ने सम्बन्धमा ।

जो जस सँग सम्बन्धित छ ।

यस शुक्लागण्डकी नगरपालिका वार्ड नं ८ अन्तर्गत ढोर व्याडमिन्टन कवर्ड हल मर्मत कार्यको लागी तपसिल बमोजिमको सामग्री खरिद गर्नुपर्ने भएको हुदाँ रितपूर्वका इच्छुक फर्म/ कम्पनी/सप्लायर्सले तपसिल बमोजिमको BOQ मा दररेट भरि तपसिल बमोजिमका कागजातहरू संलग्न गरी सुचना प्रकाशन भएको मितिले पाचै (५) दिनभित्र कार्यालय समयमा munshuklagandaki@gmail.com मा ईमेल गर्नुहुन अथवा सक्कलै कागजात खामबन्दी गरी पेश गर्नुहुन अनुरोध छ । कार्यालय समय पश्चात प्राप्त भएका दरभाउपत्र उपर कुनै कारवाही नहुने व्यहोरा समेत सुचित गरिन्छ ।

संलग्न गर्नुपर्ने कागजातहरू:

- १.स्थायी लेखा नं.प्रमाणपत्रको प्रतिलिपि ।
- २.आ.ब २०८१/०८२ को करचुक्ता पत्रको प्रतिलिपि ।
- ३.दररेट पेश गरेको निवेदन र कालो सुचिमा नपरेको स्वघोषणा पत्र ।



शिशिर पौडेल

प्रमुख प्रशासकीय अधिकृत

प्रमुख प्रशासकीय अधिकृत

सम्पर्क नं. ०६५-४१४३०५, ४१४१०५, फ्याक्स : ०६५-४१४०९८

इ-मेल : munshuklagandaki@gmail.com, वेबसाइट : www.shuklagandakimun.gov.np



SHUKLAGANDAKI MUNICIPALITY
Dulegaunda, Tanahun
Bill of Quantity (BOQ)

Project Name: Dhor Badminton Covered Hall Repair Work
Location of Project: Shuklagandaki Municipality, Ward no.8

F/Y :2082/83

S.N.	Description	Unit	Quantity	Rate Rs.		Amount	Remarks
				In Figure	In Words		
1	Providing & Fixing 4mm (not less than 3.25mm) thickness having wear layer of 0.80mm heterogeneous Acoustic PVC Vinyl Phthalate free, flooring Tarkett/Mohawk/Poly floor or equivalent brand, total weight is 3250g/m ² , PUR, No wax no polish for life (Abrasion group T: 2.00 min, residual indentation approx.0.03 mm, castor wheel test qualified, dimensional stability ≤0.40%, impact sound reduction approx +19db with acoustic improvement <65Db class A.Slip Resistance R9/R10woods, good resistance of scratch, slip, chemical and fire, a doesn't favor in growth of fungi & bacteria. 100% recyclable. Low VOC emissions after 28days of installation (lower than ≤10µg/m ³) in roll form 23running meterx200cm. Phthalate Free.Design & shades to be as per Engineer in charge on zero level floor OR after self leveling on floor till 3-3.5mm thickness of Selfleveling material of low VOC. The laid flooring should be included of Self leveling base course all complete as per the specification and instructions of engineer. Hot welded joint gives exclusively seamless finish on the floor	m ²	163.48				
				Total Rs.			
				Add 13% VAT			
				Grand Total Rs.			

Name and Address of the Firm :-

Signature and Stamp of the Firm :-

Date :-

स. तारापुष्प शिवा
 सिभिल इन्जिनियर
 NEC No. 11141 Civil 'A'

